

## LED CEILING LIGHT





























3 120	65 °C F>21lm/W 80lm/w
Model	KONS KIC9012/A
LIGHT SOURCE	СОВ
WORKING VOLTAGE	AC110V-AC220V
POWER	7W
BEAM ANGLE	15°/24°/36°
COLOR TEMPERATURE	3000K/4000K/6000K
LIGHT EFFICIENCY	>80m/W
COLOR RENDERING INDEX	Ra>85
OPERATING TEMPERATURE	-25-+40
RATED LIFE HOURS	35,000H-50,000H
LED CHIP	CREE, SAMSUNG, EPISTAR

## **DESCRIPTIONS**

- High efficiency, low energy consumption.
- Good quality beam.
- Long life span 50000 hours.
- Flexible control, Dimming by changing current
- Ecological, The waste can be recycled.
- No pollution and mercury.

## Note

- ⚠ This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.
- Do not attempt to install or use a fixture until you read and understand the installation instructions and safety labels.
- Fixtures have line voltage risk of shock and no user serviceable parts. Do not attempt to open them.
- Do not hot swap fixtures. Ensure that power to the series is off before connecting or disconnecting individual fixtures.
- Do not use a fixture if the lens, housing, or power cables are damaged.
- Do not use a fixture for any voltage for which it is not rated. Do not exceed the specified voltage and current input for any fixture.
- Caution led radiation do not stare into beam class 2 LED products.